



**UNIVERSITI PUTRA MALAYSIA**

**RHEOLOGICAL BEHAVIOUR OF COCONUT MILK: EFFECTS  
OF CONCENTRATION AND TEMPERATURE**

**NORAZIAH MUDA @ OMAR**

**FK 2002 47**

**RHEOLOGICAL BEHAVIOUR OF COCONUT MILK: EFFECTS OF  
CONCENTRATION AND TEMPERATURE**

**By**

**NORAZIAH MUDA @ OMAR**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,  
In Fulfilment of the Partial Requirement for the Degree Master of Science**

**November 2002**



*To....*

*My Parents  
who gave and nurtured*

*My Hubby  
who shared and inspired*

*My children  
to whom shall I pass*

*..... whatever is good in me*

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science

## **RHEOLOGICAL BEHAVIOUR OF COCONUT MILK: EFFECTS OF CONCENTRATION AND TEMPERATURE**

By

**NORAZIAH MUDA @ OMAR**

**November 2002**

**Chairman: Hussain bin Mohd Salleh, Ph.D.**

**Faculty : Engineering**

The rheological behaviour of coconut milk was studied using a Haake rotational viscometer having a concentric cylinder geometry sensing system. The rheological model of coconut milk, incorporating the effects of concentration and temperature was developed. Experiments were conducted at 4 levels of temperatures in the range of 5°C to 65°C and 6 levels of concentrations ranging from 10% to 50 % total solid (TS). The hysteresis effect was examined by varying the shear rate in an ascending order from  $1\text{ s}^{-1}$  to  $1000\text{ s}^{-1}$  followed by a descending order ( $1000\text{ s}^{-1}$  to  $1\text{ s}^{-1}$ ). The coconut milk, within the ranges of concentration and temperature studied, exhibited different rheological behaviours. Two rheological models, namely the Newtonian and Power Law model were applied to fit the experimental data. The coconut milk with concentrations of lower than 25% TS exhibits Newtonian behaviour. For TS of between 25% to 50%, coconut milk behaves more like a Power Law fluid. Coconut milk that exhibits Newtonian behaviour

was of low concentration while coconut milk that follows the Power Law model was of high concentration. The apparent viscosity for low concentration coconut milk showed an exponential type dependence on the concentration while the effect of temperature on the apparent viscosity obeyed the Arrhenius type relationship. The high concentration coconut milk was of a shear thinning fluid with a flow behaviour index,  $n = 0.567$ . The flow behaviour index was not significantly affected by the concentration and the temperature in the study. The effect of temperature on the consistency coefficient in Power Law model obeyed the Arrhenius type equation. The effect of concentration on the consistency coefficient obeyed an exponential type equation. The general mathematical models were developed to represent the combined effects of concentration and temperature for low concentration as well as for high concentration coconut milk. Each model developed showed accurate prediction of shear rate. The magnitude of the activation energy,  $E_a$  for low concentration coconut milk was 3720.03 cal/mol which was lower than that of high concentration coconut milk (4236.63 cal/mol). An F-test was carried out on the magnitude of shear stress for ascending and descending order shear rates for high concentration coconut milk irrespective of concentration, temperature and shear stress. The test showed that there was no significant difference in the magnitude of shear stress. This indicates that there is no significant effect of time on the rheological behaviour of coconut milk.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi sebahagian daripada keperluan untuk ijazah Master Sains

## **SIFAT RHEOLOGI BAGI SANTAN KELAPA**

Oleh

**NORAZIAH MUDA @ OMAR**

**November 2002**

**Pengerusi: Hussain bin Mohd Salleh, Ph.D.**

**Fakulti : Kejuruteraan**

Sifat rheologi bagi santan kelapa telah dijalankan dengan menggunakan viscometer berpusing bersama sistem pengesan silinder sepusat. Model rheologi bagi santan kelapa telah dibangunkan dengan mengambilkira kesan kepekatan dan suhu ujikaji terhadap sifat rheologi santan kelapa. Kajian dijalankan pada 4 tahap suhu pada julat 5-65 °C dan 6 tahap kepekatan pada julat 10-50 % jumlah pepejal keseluruhan (TS). Kadar ricih dijalankan pada aturan menaik ( $1\text{s}^{-1}$  –  $1000\text{s}^{-1}$ ) dan diikuti dengan aturan menurun ( $1000\text{s}^{-1}$  to  $1\text{s}^{-1}$ ) untuk mengkaji kesan hysteresis. Santan kelapa pada julat kepekatan yang dikaji menunjukkan sifat rheologi yang berbeza. Dua model rheologi iaitu Newtonian dan Power Law model digunakan untuk disesuaikan dengan data yang diperolehi semasa ujikaji. Santan kelapa yang berkepekatan lebih rendah daripada 25 % TS menunjukkan sifat bendalir Newtonian. Manakala, apabila kandungan jumlah pepejal keseluruhan santan kelapa yang melebihi 25% TS, santan kelapa menunjukkan sifat bendalir Power Law. Santan kelapa yang menunjukkan sifat bendalir Newtonian

dikategorikan sebagai santan kelapa berkepekatan rendah manakala santan kelapa yang menunjukkan sifat bendalir Power Law dikategorikan sebagai santan kelapa berkepekatan tinggi. Kesan kepekatan terhadap kelikatan ketara bagi santan kelapa berkepekatan rendah mematuhi persamaan berexponen manakala kesan suhu terhadap kelikatan ketara santan kelapa berkepekatan rendah ditentukan menggunakan persamaan Arrhenius. Santan kelapa berkepekatan tinggi adalah bendalir 'shear thinning' dengan indeks sifat aliran,  $n = 0.567$ . Index sifat aliran tidak dipengaruhi oleh suhu pada julat yang dikaji. Kesan suhu terhadap pekali konsisten di dalam model Power Law mematuhi persamaan Arrhenius manakala kesan kepekatan pula mematuhi persamaan berexponen. Model matematik dibentuk untuk menunjukkan kombinasi kesan suhu, kepekatan dan kadar ricih terhadap kelikatan ketara setiap satu untuk santan kelapa berkepekatan rendah dan santan kelapa berkepekatan tinggi. Nilai tenaga pengaktifan bagi santan kelapa berkepekatan rendah adalah 3720.03 kal/mol yang mana lebih rendah daripada tenaga pengaktifan bagi santan kelapa berkepekatan tinggi (4236.63 kal/mol). Analisa statistik (F-test) yang dijalankan pada nilai tekanan ricihan bagi kadar ricih aturan menaik dan menurun bagi santan kelapa berkepekatan tinggi tanpa mengambilkira kepekatan, suhu dan kadar ricih. Analisa yang dijalankan menunjukkan tiada perbezaan yang ketara bagi nilai tekanan ricihan bagi kedua-dua aturan. Ini menjelaskan bahawa kesan masa terhadap sifat rheologi santan kelapa adalah kecil dan tidak diambilkira.

## ACKNOWLEDGEMENTS

A journey is easier when you travel together. This thesis is the result of a year of work whereby I have been accompanied and supported by many people. It is a pleasant aspect that I have now the opportunity to express my gratitude for all of them.

In presenting a good deal of information in this report, the first person I would like to thank is my most helpful supervisor, Prof Madya Dr. Hussain Mohd Salleh. My million thanks to him, without whose support I would not have been able to complete this thesis. Thanks to him for monitoring my work and took effort in reading and providing me with valuable comments. Not forgetting Dr. Ibrahim Omer Mohamed for his exceptional fine assistance in planning for experiments, evaluating data as well as preparation of this thesis. I owe him lots of gratitude for having me shown this way of research. He could not even realize how much I have learned from him. I would also like to thank Dr Ibni Hajar for his excellent help and guidance. He always kept an eye on the progress of my work and always was available when I needed his advises. Also my special thanks goes to my previous supervisor Dr. Manoj Kulshreshta who always there for me when I need help.

Not forgetting other lectures in Process and Food Engineering Department, clerical staff, and technicians. I am deeply indebted for their help and their co-operation. I would like to thank to many of my friends and colleagues, for our discussions and providing me advises and tips that helped me a lot in staying at the right track and for being with me all the way through thick and thin.



Completing this task is never an easy task. I would remiss not to acknowledge the support of my husband, Mohd Ridzwan Kadir, his encouragement, patience and companionship has made it easier and smooth throughout. For three little diamonds of my heart, Sarah Imanina, Athirah Husna and Amir Husni, I was so grateful having such wonderful children like them. Their laughter and tears were my most inspiring idea in putting together the material in this thesis.

Last but not least, a million thanks to my parents, Muda @ Omar bin Salleh and Zainab Selema Binti Yusof, who formed part of my vision and taught me the good things that really matter in life. I would like to thank my brothers, sisters, nieces, nephews and family in laws for their continuing support for rendering me the sense and the value of brotherhood. I am glad to be one of them. And above all thanks to ALLAH, the most gracious and most merciful who made all this possible.

*Knowledge is a real blessing and reward to those who continually seek it.*

*Thank you and thanks again.*

I certify that an Examination Committee met on 29<sup>th</sup> November 2002 to conduct the final examination of Noraziah Muda @ Omar on her Master of Science thesis entitled "Rheological Behaviour of Coconut Milk: Effects of Concentration and Temperature" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows

**WAN MOHD HJ WAN ABDULLAH, Ph.D.**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**HUSSAIN MOHD SALLEH, Ph.D.**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**IBRAHIM OMER MOHAMED, Ph.D.**

Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**IBNI HAJAR HJ RUKUNUDIN, Ph.D.**

Director  
Mechanisation and Automation Research Centre,  
Malaysian Agricultural Research and Development Institute, MARDI  
Serdang, Malaysia  
(Member)



---

**SHAMSHER MOHAMAD RAMADILI, Ph.D.**

Professor/ Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date **29 NOV 2002**

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the partial requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

**HUSSAIN MOHD SALLEH, Ph.D.**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**IBRAHIM OMER MOHAMED, Ph.D.**

Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**IBNI HAJAR HJ RUKUNUDIN, Ph.D.**

Director  
Mechanisation and Automation Research Centre,  
Malaysian Agricultural Research and Development Institute, MARDI  
Serdang, Malaysia  
(Member)

---

**AINI IDERIS, Ph.D**

Professor/ Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## **DECLARATION**

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

---

**NORAZIAH MUDA @ OMAR**

Date:

## TABLE OF CONTENTS

	<b>Page</b>
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL SHEETS	viii
DECLARATION FORM	x
LIST OF TABLES	xiii
LIST OF FIGURES	xv
GLOSSARY OF TERMS	xvii
 <b>CHAPTER</b>	
 <b>1 INTRODUCTION</b>	 <b>1</b>
 <b>2 LITERATURE REVIEW</b>	 <b>5</b>
2.1 Coconut Milk	5
2.1.1 Coconut Milk Productions	6
2.1.2 Coconut Milk Chemistry and Compositions	8
2.1.3 Coconut Milk Processing and Preservation	10
2.1.4 Coconut Milk Product and Usage	12
2.2 Basic Concept of Food Rheology	13
2.2.1 Viscosity	13
2.2.2 Newtonian Fluid	14
2.2.3 Non Newtonian Fluid	15
2.3 Mathematical Model for Food Rheology	17
2.3.1 Time Independent Rheological Model	18
2.3.2 Time Dependent Flow Behaviour	20
2.4 Factors That Affecting the Rheological Properties of Food	24
2.4.1 Effect of Temperature	24
2.4.2 Effect of Concentration	25
2.4.3 Combine Effects Of Concentration and Temperature	26
2.5 Rheological Properties Measurements	27
2.6 Rheological Properties of Fluids and Semisolid Foods	28
 <b>3 METHODOLOGY</b>	 <b>36</b>
3.1 Materials	36
3.1.1 Raw Materials	36
3.1.2 Preparation of Samples	38
3.1.3 Measurement of Variables	40
3.1.1.1 °Brix Determination	40



3 1 1 2	Total Solid Determination	40
3 2	Rheological Measurement Equipment	41
3 3	Experimental Methodology	42
3 3 1	Preliminary Experiment	42
3 3 2	Experimental Design	43
3 4	Data Analysis	44
<b>4</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>45</b>
4 1	Rheological Data	46
4 2	Comparative Performance of Selected Rheological Model	50
4 2 1	Newtonian Model	52
4 2 2	Power Law Model	53
4 2 3	Model Selection	56
4 3	4 3 Rheological Model for Low Concentration Coconut Milk	58
4 3 1	Effect of Concentration	59
4 3 2	Effect of Temperature	60
4 3 3	Development of the General Rheological Model for Low Concentration Coconut Milk	61
4 4	4 4 Rheological Model For High Concentration Coconut Milk	64
4 4 1	Effect of Concentration	65
4 4 2	Effect of Temperature	66
4 4 3	Combined Effects of Concentration and Temperature	68
4 4 4	Development of the General Model of High Concentration Coconut Milk	69
4 5	Hysteresis Effect	73
<b>5</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	<b>75</b>
5 1	Conclusion	75
5 2	Recommendations	77
	<b>REFERENCES</b>	<b>78</b>
	<b>APPENDICES</b>	
A	Proximate Analysis Procedure	84
B	Viscometer Set Up and Specification	89
C	Statistical Analysis	95
D	Raw Data	102
	<b>VITA</b>	<b>104</b>

## LIST OF TABLES

Tables	Page
2.1 Proximate composition of undiluted whole coconut milk as reported by different sources (Seow <i>et al.</i> , 1997)	9
2.2 Chemical composition of coconut milk obtained by cold or hot water extraction at different water proportion (Cancel 1979)	9
2.3 Chemical composition of commercially canned coconut milk from different countries (Arumugam <i>et al.</i> , 1983)	11
2.4 Flow models for describing shear rate versus shear stress data for time independent flow behaviour (Rao, 1999)	18
2.5 Flow models for describing shear rate versus shear stress data for time dependent flow behaviour	22
3.1 Solid content, °Brix value and pH value of the coconut milk samples used in the study.	37
3.2 Proximate composition of undiluted M&S brand coconut milk	38
3.3 The ratio of coconut milk to the water added	39
3.4 The % °Brix of coconut milk sample used in the study	40
3.5 Summary of experimental plan	43
4.1 Parameters of Newtonian Model	51
4.2 Parameters of Power law Model	52
4.3 Parameters of exponential relationship between concentration and apparent viscosity (Equation 4.1)	60
4.4 Parameter of Arrhenius equation for effect of temperature on low concentration coconut milk (Equation 4.2)	61
4.5 Parameters of exponential relationship that relates concentration to consistency coefficient (Equation 4.6)	66

4.6	Parameter of Arrhenius equation for effect of temperature on high concentration coconut milk (Equation 4.7)	67
C-1	General format of a One Factor Analysis of Variance Table	95
C-2	One Factor Analysis of Variance Table for Shear Rate Parameter of Ascending and Descending Curve for High Concentration Coconut Milk	95
C-3	F distribution	97
D-1	Rheological data for coconut milk for ascending and descending shear rate at various concentrations at 5 °C	102
D-2	Rheological data for coconut milk for ascending and descending shear rate at various concentrations at 25 °C	102
D-3	Rheological data for coconut milk for ascending and descending shear rate at various concentrations at 45 °C	103
D-4	Rheological data for coconut milk for ascending and descending shear rate at various concentrations at 65 °C	103



## LIST OF FIGURES

Figures		Page
2.1	Representation of a Newtonian fluid flowing between a stationary plate and moving plate	14
2.2	Shear stress versus shear rate for Newtonian and Non-Newtonian Fluid	16
2.3	Behaviour of time dependant fluid (a) thixotropic, (b) rheopectic	21
4.1	Rheogram of coconut milk at 5 °C at various concentrations	47
4.2	Rheogram of coconut milk at 25°C at various concentrations	47
4.3	Rheogram of coconut milk at 45 °C at various concentrations	48
4.4	Rheogram of coconut milk at 65 °C at various concentrations	48
4.5	Typical hysteresis loop for coconut milk (concentration = 50% total solid)	49
4.6	Performance of Newtonian model at 20% total solid	51
4.7	Examination of residual of 10, 20 and 25% TS coconut milk fitted with Newtonian model	53
4.8	Examination of residual of 10, 20 and 25% TS coconut milk fitted with Power Law model	53
4.9	Performance of Power Law Model for coconut milk at (a) 5°C, (b) 25°C, (d) 45°C and, (d) 65°C	55
4.10	Comparative performance of rheological models for low concentration coconut milk (T=45°C, C=10% TS)	56
4.11	Comparative performance of rheological models for high concentration coconut milk (T=45°C, C=40% TS)	57
4.12	Effect of concentration on apparent viscosity for low concentration coconut milk at various temperatures	58

4.13	Effect of temperature on the apparent viscosity of high concentration coconut milk at various concentrations	59
4.14	Plot of residual versus observed shear rate for regression of equation 4.3 for concentration $\leq 25\%$ TS	63
4.15	Plot of observed shear rate against experimental shear rate for low concentration coconut milk for regression of equation 4.3	63
4.16	Combined effect of concentration and temperature on the flow behaviour index, $n$	68
4.17	Combined effect of concentration and temperature on the consistency coefficient, $K$	69
4.18	Plot of residual versus observed shear rate for regression of equation 4.8 for concentration 25 –50% TS	71
4.19	Plot of observed shear rate against experimental shear rate for high concentration coconut milk for regression of equation 4.8	71
B-1	Haake Rheowin Job Manager – Main Page	90
B-2	Haake Rheowin Job Manager -Device Manager	90
B-3	Haake Rheowin Job manager –Lift Control Manager	91
B-4	Haake Rheowin Job manager –Temperature Setting	92
B-5	Haake Rheowin Job manager –Measurement Element Parameter	93
B-6	Haake Rheowin Job manager –Measurement Element Acquisition	93
C-1	The F distribution for ascending and descending curve parameter indicating the critical value at 5% level of significance	96

## GLOSSARY OF TERMS

### Roman Letters

A	Shear rate at the beginning of shearing of equation 2.3, Pa
a	Constant in equation 4.1
$a_k$	Constant in equation 4.6
APPC	Asia and Pacific Coconut Community
Asc	Ascending order shear rate
B	Rate of structural breakdown of equation 2.3, $s^{-1}$
b	Constant in equation 4.1
$b_k$	Constant in equation 4.6
C	Concentration
Des	Descending order shear rate curve
$dv/dy$	Velocity gradient, $s^{-1}$
e,f,g and h	Model parameter for equation 2.13
$E_a$	Activation energy, Cal/mol
F	Force, $kg/m^2$
$F_o$	Process time at 121.1 °C (250° F), min
Ha	Hectare
K	Consistency coefficient in Power law model, $(Pa.s^n)$
$k_1$	Rate constant
N	Flow behaviour index in Power law mode
Pa	Pascal
psi	Pound per square inch
R	Universal Gas constant ( $cal\ mol^{-1}\ K^{-1}$ )
$R^2$	Coefficient of determination (dimensionless)
s	Second
T	Absolute temperature (Kelvin)
t	Time (sec.)
TS	Total solid

$T_{s_f}$	Final total solid content, %
$T_{s_i}$	Initial total solid content, %
$v$	Velocity, m/s
$W_b$	Weight of sample before drying, g
$W_d$	Weight of sample after drying, g
$W_i$	Initial weight, g
$y$	Distances between two plates, m

#### **Greek letters**

$\alpha$	Constant
$\tau$	Shear stress, Pa
$\tau_o$	Yield stress, Pa
$\lambda$	Time dependent structural parameter
$\lambda_e$	Equilibrium time dependent structural parameter
$\eta$	Viscosity, Pa s
$\eta_a$	Apparent viscosity, Pa s
$\eta_o$	References viscosity, Pa s
$\dot{\gamma}$	Shear rate, $s^{-1}$
$\beta$	Constant
$\mu$	Dynamic viscosity, Pa s

## CHAPTER 1

### INTRODUCTION

Coconut milk is becoming an increasingly important raw material in home cooking as well as in the food processing industries. It is extracted from the solid coconut endosperm. It is estimated that 25% of the world coconut output is consumed as coconut milk (Gwee, 1988). Coconut milk is a major and an essential ingredient in the preparation of a wide variety of food products such as curry, desserts, coconut jam spread, coconut syrup, coconut cheese, bakery products, beverages and coconut tofu (Gonzales, 1986; Gwee, 1988). When combined with skim milk (cow's milk), a new product with a good commercial potential is developed (Seow and Gwee, 1997). It can also be used as a substitute for milk in some desserts. Chocolate and other confectionaries are exotically flavoured with coconut milk.

In commercial production, coconut milk is extracted by pressing grated coconut endosperm using the hydraulic or the screw press (Cancel, 1979). The milk is then filtered through a cloth filter or centrifuged at low speeds to remove finely comminute particles of coconut pulp without breaking the emulsion. The result is a milky white, opaque emulsion with a sweet coconut flavour.

Untreated coconut milk spoils rapidly even under chilled storage. It is a very rich medium which can support the growth of the common spoilage microorganisms (Seow and Gwee, 1997). Over the years, many attempts have been made to commercially

extend the shelf life of coconut milk through canning, aseptic packaging and spray drying. The manufacturing processes of canned and aseptic packaging of coconut milk involves heat treatment for sterilization and pasteurisation and under continuous flow in the pipeline. The coconut milk is pumped and sheared prior to being filled into the container. The mechanical handling of coconut milk involves both the deformation and the flow of a material and these mechanical properties are referred to as rheological properties.

Rheology is defined as a science of flow and deformation of matter and describes the interrelationships between force, deformation and time (Rao, 1999). The term comes from the Greek words *rheos* meaning to flow. Normally, deformation pertains to solid, and flow to liquid. Despite the fact that the rheology of fluid and semisolid food had established a growing interest during the last few years, there is a need to appreciate the basic principals of rheological behaviour and proper measurement of rheological properties as well as the influence of composition and structure on those properties.

Rheological properties of food material in processing are important in the design of flow processes, quality control, storage, processing stability of measurement and predicting texture (Davis, 1973). Rheological data is essential in optimising equipment design, ensuring adequate heat treatment and limiting overheating of product in food exposed to thermal processing conditions (Anderson *et al.*, 1999), evaluating heating rates during such engineering operation as in aseptic processing (Rao, 1999), as well as to estimate velocity, shear and residence time distribution in extrusion and continuous mixing (Kokini, 1992).

The knowledge of rheological properties is also important in the development phase of a new product, relating the properties with sensory towards understanding consumer perceptions of food texture, provide important measurement to facilitate process design and development and in selecting on line measurement technique (Borwankar, 1992).

Food, in general cannot be categorised as simply solid or liquid. They are usually classified as solids, gels, homogeneous liquids, suspension of solids in liquids and emulsions. Fluid foods are those that do not retain their shape but take the shape of their containers. Fluid foods that contain significant amounts of compounds and suspended solids exhibit non-Newtonian behaviours. Many non-Newtonian behaviour are characterized by both viscous and elastic properties called visco-elastic behaviour. Since fluids and semisolid foods exhibit a wide variety of rheological behaviours ranging from Newtonian to time dependent, dilatants, thixotropy etc (Rao, 1999), the understandings of these rheological behaviours are of considerable importance..

Dynamic rheological testing is used to characterize visco-elastic properties of foodstuffs. It involves subjecting the test sample to a cyclic loading in where the stress and the strain vary harmonically with time. Dynamic testing is a non-destructive technique for investigating the structure of foods. Using this technique, several useful rheological parameters can be obtained which quantify the visco-elastic characteristics of the material.

Studies on the rheological characteristics of coconut milk have not been explored widely. Despite the fact that coconut milk is an indispensable ingredient in many of the traditional cuisines especially of South East Asian countries, information on its rheological behaviour is very important. The rheological data over the range of temperature would provide insight into rheological characteristic of the coconut milk, which is essential for pumping system and equipment design and analysis of various processes. The rheological data on coconut milk at different concentrations are also essential because varying the coconut milk concentration often lead to dramatic changes in their viscoelastic behaviour. The applications of the coconut milk are also varied depending on their concentrations, for instance, thick coconut milk normally use for making dessert while thin coconut milk is use for light curries or puddings.

The rheological data of coconut milk at different concentrations and temperatures are essential in the design of pumping systems, the analysis of various processes, the design of equipments and machineries, the formulation of new products and the control of quality. This study intends to contribute useful data to the field of rheology, particularly those relating to coconut milk. The objectives of this study are:

- 1) to study the effect of temperature and concentration on the rheological behaviour of coconut milk;
- 2) to develop a rheological model for coconut milk as a function of concentration and temperature;
- 3) to study the effect of time on the rheological behaviour of coconut milk by examining the hysteresis effect.



## CHAPTER 2

### LITERATURE REVIEW

The science of food rheology had advanced considerably during the past few decades. Numerous rheological studies on various foodstuffs can be found in the literature. The basic concept of rheology, various mathematical models, rheological instrument and measurement technique and factors that influence the rheological properties of food product has been reviewed and discussed in the following sections. In addition, general information on coconut milk and its product is also presented. Finally major studies on the rheological properties of different fluid and semisolid food is reviewed.

#### 2.1 Coconut Milk

Coconut milk is a generic term for the aqueous extract from solid endosperm of coconut (*Cocos nucifera*). Although oil recovery is the major concern in the coconut industry, there appears to be increasing demand for the coconut milk extract for use in home and in the food industries. In Malaysia, as per information from Asia and Pacific Coconut Community (APPC), the total coconut plantation in Malaysia in 2000 was 230000 Ha. (Ministry of Primary Industry, 2001). Those cultivated coconuts were exported in the form of fresh coconut, copra, coconut oil, desiccated coconut, coconut milk, and other coconut by-product. About 0.8 % of the total export earning, which is equivalent to 2181 million tones per annum, was exported in the form of coconut milk. It has also been